

BMW R NineT 1200 (K21) my 14/16

product	code	description
Steering damper kit	SD.B304K	SDK (stock)
Steering damper kit	SD.B304R	SDR (stock)
Monoshock (R-L-P)	MB315.2KD	M46KD std
Monoshock (R-L-HP)	MB315.2KDID	M46KD+ID hydraulic spring preload
Monoshock (R-L-HP)	MB315.2KDIK	M46KD+IKD knob-hydraulic spring preload
Monoshock (C-R-L-P)	MB315.06K	M46K std
Monoshock (C-R-L-HP)	MB315.06ID	M46K+ID hydraulic spring preload
Monoshock (C-R-L-HP)	MB315.06IK	M46K+IKD knob-hydraulic spring preload
Monoshock (CH-CL-R-L-HP)	MB315.06R	M46R (ID hydraulic spring preload)
Monoshock (CH-CL-R-L-HP)	MB315.06RK	M46R (IKD knob-hydraulic spring preload)
Fork kit (C-R-P) (fork Sachs)	F20B307K	F20K "quad valve" Hydraulic Cartridge kit (1)
Fork kit (C-R-P) (fork Sachs)	F20B308K	F20K "quad valve" Hydraulic Cartridge kit (2)
Fork kit (C-R-P) (fork Sachs)	F25B307R	F25R "quad valve" Hydraulic Cartridge kit (1)
Fork kit (C-R-P) (fork Sachs)	F25B308R	F25R "quad valve" Hydraulic Cartridge kit (2)



CH = HighSpeed Comp. adj. / regolazione Compresine AV
 CL = LowSpeed Comp. adj. / regolazione Compresione BV
 C = Compression adj. / regolazione Compresione
 R = Rebound adj. / regolazione Estensione
 L = Length adj. / regolazione Interasse
 P = spring Preload / Precarico molla
 HP = hydraulic spring Preload adj. / Precarico molla idraulico

BMW R NineT 1200 (K21) my 14/16



Note: (1) *Street Version* = stroke 105 mm (2) *Sport version* = stroke 120 mm

Quad-valve asymmetric system



Compression unit with reference clicks
(range: 38 clicks)

Preload unit assembled on axial roller bearings,
(range: 15 mm)

Rebound unit with reference clicks
(range: 38 clicks)

on demand
the technopolymer fork cap tools

T21 fork cap tool 36 (8 sides)



T22 fork cap tool 28 (6 sides)

