

KAWASAKI ZX 6R 636 my 13/18

product	code	description
Steering damper kit	SD.K122K	SDK (front)
Steering damper kit	SD.K122R	SDR (front)
Monoshock (R-L-P)	MK120.1KD	M46KD std
Monoshock (R-L-HP)	MK120.1KDIS	M46KD+IS hydraulic spring preload
Monoshock (C-R-L-P)	MK120.11K	M46K std
Monoshock (C-R-L-HP)	MK120.11P	M46K+P2 flex-hydraulic spring preload
Monoshock (CH-CL-R-L-HP)	MK120.11R	M46R racing (P2 preload unit)
Fork kit (fork type Showa SFF)	FK120RK-BP1	FRK Hydraulic kit
Fork kit (C-R-P) (fork type Showa SFF)	F20K120K	F20K "quad valve system" Hydraulic Cartridge kit
Fork kit (C-R-P) (fork type Showa SFF)	F25K120R	F25R "quad valve system" Hydraulic Cartridge kit
Fork kit (C-R-P) (fork type Showa SFF)	F25K120SA	F25SA "sealed" Hydraulic Cartridge kit



CH = HighSpeed Compression adj. / regolazione Compresse AV
 CL = LowSpeed Compression adj. / regolazione Compresse BV
 C = Compression adjustment / regolazione Compressione
 R = Rebound adjustment / regolazione Estensione
 L = Length adjustment / regolazione Interasse
 P = standard spring Preload by ring / Precarico molla standard
 HP = hydraulic spring Preload adj. / regolazione Precarico molla idraulico

KAWASAKI ZX 6R 636 my 13/18



Rebound unit
(range: 38 clicks)

Preload unit
(range: 15 mm)

Compression unit
(range: 38 clicks)

F25SA fork kit



Quad-valve asymmetric system



Compression unit
(range: 38 clicks)

Preload unit
(range: 15 mm)

Rebound unit
(range: 38 clicks)



F25R fork kit



Quad-valve asymmetric system



Compression unit
(range: 38 clicks)

Preload unit
(range: 15 mm)

Rebound unit
(range: 38 clicks)



FRK-BP1 Fork kit

F20K fork kit



SD-R

SD-K