

KAWASAKI ZX 6R 636 my 24/-

product	code	description
Steering damper kit	SD.K124K	SDK (front)
Steering damper kit	SD.K124R	SDR (front)
Monoshock (R-L-P)	MK147.1KD	M46KD std
Monoshock (R-L-HP)	MK147.1KDIS	M46KD+IS hydraulic spring preload
Monoshock (C-R-L-P)	MK147.11K	M46K std
Monoshock (C-R-L-HP)	MK147.11P	M46K+P2 flex-hydraulic spring preload
Monoshock (CH-CL-R-L-HP)	MK147.11R	M46R racing (P2 flex preload unit)
Fork kit (fork type Showa SFF)	FK141RK-BP2	FRK Hydraulic kit (step2)
Fork kit (C-R-P) (fork type Showa SFF)	F20K141K	F20K "quad valve system" Hydraulic Cartridge kit
Fork kit (C-R-P) (fork type Showa SFF)	F25K141R	F25R "quad valve system" Hydraulic Cartridge kit
Fork kit (C-R-P) (fork type Showa SFF)	F25K141SA	F25SA "sealed" Hydraulic Cartridge kit



Dark Series (on demand)



High speed
Low speed
Compression
adjustment
+ -



Compression
adjustment
+ -



Flex-Hydraulic
Preload
adjustment
+ -



Hydraulic
spring
preload unit
+ -



Rebound
adjustment
+ -

Length
adjustment
+ -



CH = HighSpeed Compression adj. / regolazione Compresine AV
CL = LowSpeed Compression adj. / regolazione Compresione BV
C = Compression adjustment / regolazione Compresione
R = Rebound adjustment / regolazione Estensione
L = Length adjustment / regolazione Interasse
P = spring Preload / Precarico molla
HP = hydraulic spring Preload / Precarico molla idraulico

KAWASAKI ZX 6R 636 my 24/-



F25SA Sealed cartridge asymmetric system



Rebound unit
(range: 38 clicks)



Preload unit
(range: 15 mm)

Compression unit
(range: 38 clicks)



F25R Quad-valve asymmetric system



Compression unit
(range: 38 clicks)

Preload unit
(range: 15 mm)



Rebound unit
(range: 38 clicks)



on demand
the technopolymer fork cap tools

T21 fork cap tool 36 (8 sides)



T22 fork cap tool 28 (6 sides)



F20K Quad-valve asymmetric system



Compression unit
(range: 38 clicks)



Preload unit
(range: 15 mm)

Rebound unit
(range: 38 clicks)



FRK-BP2 Fork kit



SD-R

SD-K

